

Modelo		ADT26UX4RSBL8	ADT35UX4RSBL8	ADT52UX4RJCL8	AUD71UX4RKFM8		AUD105UX6RNEH8	AUD125UX6RNEH8	AUD140UX6RNEH8	AUD200UX6RZPH8	AUD250UX6RZPH8
Unidad interior		ADT26UX4RBL8	ADT35UX4RBL8	ADT52UX4RCL8	AUD71UX4RFM8		AUD105UX4REH8	AUD125UX4REH8	AUD140UX4REH8	AUD200UX4RPH8	AUD250UX4RPH8
Unidad exterior		AUW26U4RS8	AUW35U4RS8	AUW52U4RJ8	AUW71U4RK8		AUW105U6RN8	AUW125U6RN8	AUW140U6RN8	AUW200U6RZ8	AUW250U6RZ8
Capacidad											
Capacidad frigorífica nominal (Mín.-Máx.)	kW	2,6 (1,3-3,6)	3,5 (1,3-4,2)	5,0 (1,5-7,0)	7,0 (2,0-9,0)		10,0 (2,7-12,0)	12,1 (3,9-13,2)	13,5 (4,3-15,5)	19,0 (7,0-23,5)	23,0 (7,5-24,5)
Capacidad calorífica nominal (Mín.-Máx.)	kW	3,2 (1,3-4,0)	4,0 (1,3-5,0)	5,5 (1,5-7,3)	8,0 (2,0-10,2)		11,0 (2,7-13,0)	13,5 (3,4-14,4)	16,0 (3,7-17,1)	22,0 (6,0-25,0)	25,0 (6,5-27,5)
Consumo nominal											
Refrigeración	kW	0,59	0,87	1,28	1,75		2,63	3,67	4,65	6,33	9,78
Calefacción	kW	0,74	1,00	1,33	1,97		2,75	3,64	4,70	5,86	7,24
Coeficiente energético											
SEER		7,2	7,0	7,0	7,2		7,0	6,2	6,1	6,0	5,8
SCOP		4,3	4,3	4,6	4,6		4,4	4,3	4,3	3,9	3,9
Clasificación energética											
Refrigeración		A++	A++	A++	A++		A++	-	-	-	-
Calefacción		A++	A++	A++	A++		A+	-	-	-	-
Unidad interior											
Caudal de aire (A/M/B)	m3/h	600/484/400	600/484/400	900/840/780	1360/1150/1000		2000/1800/1600	2400/2200/1900	2400/2200/1900	4400/3900/3400	4400/3900/3400
Presión sonora (A/M/B)	dB (A)	36/33/30	36/33/30	41/37/33	40/37/34		42/39/36	43/40/37	43/40/37	58/55/52	58/55/52
Potencia sonora	dB (A)	50	50	57	56		59	63	64	81	81
Dimensiones (An x Al x Pr)	mm	910×190×447	910×190×447	1180×190×447	1100×245×700		1400×300×800	1400×300×800	1400×300×800	1400×420×858	1400×420×858
Peso Neto/con embalaje	kg	18,0/21,5	18,0/21,5	24,5/29,5	33,0/39,0		53,0/59,0	53,0/59,0	53,0/59,0	84,0/93,5	84,0/93,5
Presión estática externa Nominal (Rango)	Pa	35 (0~50)	35 (0~50)	35 (0~50)	100 (0~150)		100 (0~200)	100 (0~200)	100 (0~200)	150 (0~250)	150 (0~250)
Unidad exterior											
Alimentación		220-240V~,50&60Hz,1P	220-240V~,50&60Hz,1P	220-240V~,50&60Hz,1P	220-240V~,50&60Hz,1P		380-415V~,50&60Hz 3P	380-415V~,50&60Hz 3P	380-415V~,50&60Hz 3P	380-415V~,50&60Hz 3P	380-415V~,50&60Hz 3P
Presión sonora	dB (A)	51	51	53	56		57	58	58	61	61
Potencia sonora	dB (A)	62	62	64	68		68	69	70	76	76
Dimensiones (An x Al x Pr)	mm	810×580×280	810×580×280	860×670×310	900×750×340		900×1170×320	900×1170×320	900×1170×320	1100×1650×390	1100×1650×390
Peso	Kg	34	34	44	53		81	83	83	140	140
Caudal de aire	m3/h	2300	2300	3150	3800		5500	5500	5500	11500	11500
Refrigerante											
Refrigerant gas		R32	R32	R32	R32		R32	R32	R32	R32	R32
Refrigerant precarga	kg	0,87	0,87	1,20	1,50		2,80	3,00	3,00	4,60	4,60
TCO2 eq		0,587	0,587	0,810	1.013		1.890	2.025	2.025	3.105	3.105
Diámetro tuberías											
Líquido/gas	mm/pulg	1/4"/3/8" (6,35/9,52)	1/4"/3/8" (6,35/9,52)	1/4"/1/2" (6,35/12,7)	3/8"/5/8" (9,52/15,88)		3/8"/5/8" (9,52/15,88)	3/8"/5/8" (9,52/15,88)	3/8"/5/8" (9,52/15,88)	3/8"/7/8" (9,52/22,22)	3/8"/7/8" (9,52/22,22)
Rango de operación											
Tª ext. para refrigeración	°C	-15 ~ 52	-15 ~ 52	-15 ~ 52	-15 ~ 52		-15 ~ 52	-15 ~ 52	-15 ~ 52	-15 ~ 50	-15 ~ 50
Tª ext. para calefacción	°C	-20 ~ 24	-20 ~ 24	-20 ~ 24	-20 ~ 24		-20 ~ 24	-20 ~ 24	-20 ~ 24	-20 ~ 24	-20 ~ 24
Longitud de la tubería											
Longitud máxima	m	30	30	50	50		50	60	60	75	75
Diferencia de altura											
Max. (OD más baja)	m	15	15	30	30		30	30	30	30	30
Max. (OD más alta)	m	15	15	30	30		30	30	30	30	30
Longitud de tubería máxima con precarga											
Distancia	m	5	5	5	5		7,5	7,5	7,5	7,5	7,5
Carga adicional de refrigerante											
Cantidad adicional por m	g/m	15	15	15	35		35	35	35	35	35